



## → PLATFORM SPECIFICATIONS

| <u>PARAMETER</u>               | <u>DESCRIPTION</u>  |
|--------------------------------|---|
| <b>Dimensions w/o Carriage</b> | 60x47x23.5 in / 150x120x60 cm   |
| <b>With Carriage</b>           | 76x47x40 in / 195x120x105 cm  |
| <b>Military Standards</b>      | Ruggedized, IP67  |
| <b>Weight</b>                  | 900 lbs (410 kg) including carriage   |
| <b>Max Payload Weight</b>      | 1,500 lbs (700 kg)  |
| <b>Speed</b>                   | 6 mph / 9.6 kph   |
| <b>Communication</b>           | Secure IP Mobile Ad-hoc network   |
| <b>Operating Range</b>         | Up to 1,600 ft (500 m) LOS, with standard operating gear  |
| <b>Operational Time</b>        | 8 hours   |
| <b>Payload Ports</b>           | External Power, Ethernet RJ45, GPS ant, RF ant, IOP 12V,24V,28V, NATO Recepticle  |
| <b>GPS</b>                     | External  |
| <b>Video &amp; Cameras</b>     | 360° Real time day & night video  |
| <b>Illumination Module</b>     | 360° NIR illumination   |
| <b>Operation Mode</b>          | Dedicated Joystick & ROCU®-7 Ruggedized Control & Display Unit <ul style="list-style-type: none"> <li>• Follow me kit</li> <li>• GPS waypoint navigation</li> <li>• 50 mph</li> </ul> |
| <b>Towing Capabilities</b>     |   |
| <b>Hybrid Mode</b>             |   |

